



## General Technical Data

Engine type:	four-stroke, direct-injection
Cylinders:	12 cylinder in V-form, wet replaceable cylinder liners
Aspiration:	turbocharger, intercooler
Cooling:	water circulation by centrifugal pump on engine
Lubrication:	force-feed lubrication by gear pump, lubricating oil cooler in cooling water circuit of engine
Injection:	Common Rail System 1800 bar, Type EDC7 C32
Generator:	three-phase generator 28V /120A
Starter motor:	starter 105P70 24V / 7 kW

## POWERED BY:



### GENERATING SET MODEL (EP 940)

Output Ratings	Prime (PRP)	Standby (ESP)
400 V, 3 ph, 50 Hz, 1500 rpm	940KVA	1000 KVA
	752KW	800KW
480 V, 3 ph, 60 Hz, 1800 rpm	1000KVA	1100 KVA
	800 KW	880KW

Alternators ratings may change at different voltages.

Ratings at 0.8 Power Factor

### ENGINE / TECHNICAL DATA

Engine Make	MAN			
Engine Model	D2862LE231			
Governing Type	ISO 8528-5:2005G3			
Number of Cylinders	12			
Cylinder Arrangement	V-Form			
Bore and Stroke mm	128 x 157			
Displacement / Cubic Capacity litres	24.2			
Induction System	Turbocharged and Intercooled			
Cycle	4 stroke			
Combustion System	Direct Injection			
Compression Ratio	17.0:1			
Rotation	Counter-clockwise, viewed on flywheel			
Cooling System	Water - cooled			
Frequency and Engine Speed	50Hz & 1500rpm		60Hz & 1800rpm	
	Prime(PRP)	Standby(ESP)	Prime(PRP)	Standby(ESP)
Mechanical Power Output kW	800	880	836	920
Fuel Consumption@100%load(g/kWh)	188	188	194	194
Fuel consumption @75%load (g/kWh)	189	188	194	194
Fuel consumption @50%load (g/kWh)	192	191	198	197
Total Lubrication system capacity litres	70	70	70	70
Total Coolant Capacity litres	117	117	117	117
Exhaust gas volume flow(m3/h)	7620	8071	8511	9148
Air for Combustion -Volume flow (m3/h)	2910	3030	3347	3456
Starter battery capacity (Ah)	180(24V)	180(24V)	180(24V)	180(24V)
Dimensions for open set (LXBXH)in mm	4000x2170x1561			
Dimensions for silent set (LXBXH)in mm	6040x2420x2540			

### ALTERNATOR DATA

Make	Leroy Somer
Model	TAL 049E
No. of bearings	1
Insulation class	H
Total Harmonic Content	<3.5% on load
Wires	6
Ingress Protection	IP23
Excitation System	SHUNT
Winding Pitch	2/3 (n° 6)
AVR Model	R150
Overspeed	2250 mn <sup>-1</sup>
Voltage Regulation (steady)	± 1%
Short Circuit Capacity	-

AREP & PMG Excitation System Available as Optional.

### CONTROL PANEL

Make	Deep Sea
Model	DSE7320

DSE7320 is an Auto Mains (Utility) Failure Control Module. It is operated via the START, STOP, AUTO and MANUAL soft touch membrane buttons on the front panel. DSE7320 can be controlled remotely using either a GSM Modem, Ethernet via DSE860/865 or via RS485.

#### Protection:

- Fail to start
- Low oil pressure
- High engine temperature
- U/O Voltage shutdown
- U/O Frequency shutdown
- Underspeed, Overspeed
- Loss of engine speed detection
- High/Low battery voltage
- kW overload
- Unbalanced load
- Low fuel alarm (if fitted)
- Battery charger failure (if fitted)



POWERED BY:



## RATINGS DEFINITION

### Prime Power (PRP):

- Power output available with varying load for unlimited time. Average power output is 80 % of the prime power rating .
- With 10 % overload capability for technical purposes for a maximum of one hour in twelve Overload operation cannot exceed 50 hours per year.
- Prime power in accordance with ISO 8528.
- Fuel stop power in accordance with ISO 3046.

### Emergency Standby Power (ESP)

- Power output available with varying load for the duration of an emergency outage power output is 70 % of the emergency standby.Average power rating .
- Typical operation is 50 hours per year with maximum expected usage of 200 hours per year.
- Standby power in accordance with ISO 8528.
- Fuel stop power in accordance with ISO 3046.

## STANDARD REFERENCE CONDITIONS

Output ratings are presented at 25°C air inlet temperature, barometric pressure 100 kPa, relative humidity 30%. This generating set is designed to operate at high ambient temperatures (up to 55°C), humidity (up to 99%) and higher altitudes. De-ration may apply, please consult your dealer for specific site ratings.

Some of the specifications are not standard on all Genset models.

## AVAILABLE OPTIONS & ACCESSORIES

We offer a range of optional features and accessories to tailor our generating sets to meet your power needs.

### OPTIONS

- A variety of generating set control and synchronizing panels
- Additional protection alarms and shutdowns
- Water fuel separator
- Water jacket heater
- Battery charger

### ACCESSORIES

- Genuine spare parts
- Load banks
- Auxiliary fuel tanks
- Manual & automatic transfer switches

For further information on all of the standard and optional features accompanying this product please contact your local dealer or visit [www.alhuthelilymotors.com](http://www.alhuthelilymotors.com)

## STANDARD SPECIFICATIONS

### 1. ENGINE

MAN four stroke heavy duty high performance industrial type diesel engine.

### 2. TROPICAL COOLING RADIATOR

Radiator and cooling fan, complete with safety guards, designed to cool the engine at high ambient temperatures (consult your dealer for de-ration factors)

### 3. CIRCUIT BREAKER TYPE

3 pole MCCB/ACB (4 pole is optional)

### 4. ALTERNATOR

#### 4.1 INSULATION SYSTEM

- The insulation system is Class H.
- All windings are impregnated in either a triple dip thermosetting liquid, oil and acid resisting polyester varnish or vacuum pressure impregnated with a special polyester resin.
- Heavy coat of antitracking varnish additional protection against moisture or condensation.

#### 4.2 AUTOMATIC VOLTAGE REGULATOR (AVR)

The fully sealed Automatic Voltage Regulator maintains the Voltage Regulation at  $\pm 1\%$ . Nominal adjustment by means of a trim pot incorporated on the AVR.

### 5. MOUNTING ARRANGEMENT

#### 5.1 BASE FRAME

The complete Generating Set is mounted as a whole on a heavy duty fabricated steel Baseframe.

#### 5.2 COUPLING

The Engine and Alternator are directly coupled by means of an SAE flange. The Engine flywheel is flexibly coupled to the Alternator rotor.

#### 5.3 ANTI-VIBRATION MOUNTING PADS

Anti-Vibration pads are affixed between the Engine / Alternator feet and the Baseframe thus ensuring complete vibration isolation of the rotating assembly.

#### 5.4 SAFETY GUARDS

The Fan & Fan Drive along with the Battery Charging Alternator are Safety Guard protected for personnel protection.

### 6. FACTORY TESTS

- The Generating set is load tested before dispatch
- All protective devices control functions and site load conditions are simulated. The generator and it's systems are checked before dispatch.

### 7. EQUIPMENT FINISHING

All mild steel components are fully degreased and painted with powder coated paint to ensure maximum scuff resistance and durability.

### 8. DOCUMENTATIONS

Operation & Maintenance manual, Circuit wiring diagrams and Commissioning / Fault Finding instruction leaflets are accompanied with the Generator.

### 9. WARRANTY

MAN engines are covered under a warranty policy for a period of 24 months. Warranty of the complete genset is in line with manufacturers standard warranty terms & conditions.

(check warranty statement for more details, as it may vary for different countries)

### 10. QUALITY STANDARDS

The equipment meets the following standards: BS4999, BS5000, BS5514 IEC 60034, VDE0530, NEMA MG 1.22 and ISO 8528.